

# LED FLAME-PROOF LED LIGHT FITTING PLANT/STREET LIGHT



### **APPLICATIONS & FEATURES**

Applied to oil company, Refineries, Offshore & Onshore Oil Platform, Solvent, Chemical, Pharmaceuticals, Gas Filling stations, Oil Tanks, All the Hazardous area Etc. suitable for Zone 1, 21 & 2, 22 Gas Gr. IIB

- Branded LED & drivers with High class light Efficiency. CITIZEN LED Chip, PDC Casting al. Alloy LM6 housing, with Epoxy Polyester powder coating.
- Min. power consumption while high light efficiency, power consumption just 20% as much as HPMV/SV/MHL lamp at the same luminous condition, it saves energy more than 75% than that traditional light.
- Advanced quadratic light distribution design result in high uniformity of illuminations and good lighting quality, clear lighting effect without a double image.
- Beautiful appearance, several type of installation methods available.

### **CAT NO - TFE-LED-03**

+ Type of Ex Protections : Ex d+ Ingress protections : IP66

Zone classification : Zone 1,21 & 2, 22

Gas Group : IIA, IIB,

MOC : PDC Al. Alloy LM6
Finish : EP Powder Coat
O' Ring : Neoprene Rubber
Glass : Toughened Glass

Hardware : SS Cable Entry : M20 -02 Nos.

Ex Marking : Ex d IIB IP66 T6
Certification : CIMFR, BIS, PESO



# **PRODUCT SPECIFICATIONS**

Rated Power	UPTO 120 Watt
Input Voltage	110-220 VAC
Beam Angle	120 Dgree
Total Lumen	110lm/w
Color Temperatures	6500K
CRI	>80
Power Factor	>0.95
Temp. Class	T5 with -40 to 90 C
Lifetime	>50000Hrs.
Protection	OV/SC/ Surge 10KV
THD	Less Than 10%
lk07 Tested	Yes Available
Efficiency of driver	> 85%
LED Certification	Lm80 & LM79

#### TRI-FLP ENGINEERS PVT. LTD.

Gala No 7, Gulmohar Park, Plot No A-164, 165, MIDC, Phase-I, Near Bhavana Transport, Opp Suzuki Service Dombivali E, Dist Thane 421204, Maharashtra, India.

Tel: +91 0251 2433393 / 2452001 / 2440071 / 2440081

Email: vikas@trimurtitriflp.com / triflp@gmail.com


Web: www.explosionproof.co.in








## **AAI Figure (Lux Distance Curve)**




309.95cm 1729.0, 1438.0I 619.90cm 432.2, 359.5b 192.1, 159.8lx 929.85cm 108.1, 89.9lx 1239.80cm 1549.75cm 69.2, 57.51 5.0m Max/Ave Beam Angle of C0plane 114.33°


60 Watt

40 Watt






# **Examples of Mounting**



**Wall / Ceiling Mounting** 



**Pole Mounting Bracket** 

### TRI-FLP ENGINEERS PVT. LTD.

Gala No 7, Gulmohar Park, Plot No A-164, 165, MIDC, Phase-I, Near Bhavana Transport, Opp Suzuki Service Dombivali E, Dist Thane 421204, Maharashtra, India.

Tel: +91 0251 2433393 / 2452001 / 2440071 / 2440081

Email: vikas@trimurtitriflp.com / triflp@gmail.com

Web: www.explosionproof.co.in

